











Pressverbindungen

	Artikel-Nr.	Bestell-Nr.	Preis %	Pack-Norm	Summe der Leiterquerschnitte	Hauptanwendungsbereich
Kupfer-Presshülsen						
	07	25019.22	7,80	500	> 3,0 - 6,0 mm ²	3 x 1,5 mm ² / 4 x 1,5 mm ² / 2 x 2,5 mm ²
	30	25019.18	9,50	500	> 4,0 - 7,5 mm ²	3 x 1,5 mm ² / 4 x 1,5 mm ² / 5 x 1,5 mm ² 2 x 2,5 mm ² / 3 x 2,5 mm ²
	08	25019.23	9,50	500	> 6,0 - 10,0 mm ²	3 x 2,5 mm ² / 4 x 2,5 mm ² / 2 x 4,0 mm ² 5 x 1,5 mm ² / 6 x 1,5 mm ² / 7 x 1,5 mm ²
	09	25019.24	13,00	500	> 10,0 - 18,0 mm ²	3 x 4,0 mm ² / 4 x 4,0 mm ² / 2 x 6,0 mm ²
Aluminium-Presshülsen						
	18	25019.3	4,50	500	> 4,0 - 6,0 mm ²	2x2,5 ² Al / 1x2,5 ² Al, 1x2,5 ² Cu 1x2,5 ² Al, 1x1,5 ² Cu / 1x2,5 ² Al, 2x1,5 ² Cu
	01	25019.4	4,50	500	> 6,0 - 7,5 mm ²	3x2,5 ² Al / 2x2,5 ² Al, 1x2,5 ² Cu 2x2,5 ² Al, 1x1,5 ² Cu / 1x2,5 ² Al, 3x1,5 ² Cu
	02	25019.5	4,50	500	> 8,0 - 10,0 mm ²	4x2,5 ² Al / 3x2,5 ² Al, 1x2,5 ² Cu 2x2,5 ² Al, 2x2,5 ² Cu / 3x2,5 ² Al, 1x1,5 ² Cu
	04	25019.7	5,50	300	> 14,0 - 17,0 mm ²	4 x 4,0 mm ² Al / 6 x 2,5 mm ² Al
	06	25019.17	7,50	250	> 23,0 - 28,0 mm ²	4 x 6,0 mm ² Al 6 x 4,0 mm ² Al / 7 x 4,0 mm ² Al
Isolierhülsen						
	10	25019.8	2,80	500	Leiter 2,5 mm ²	für Presshülsen Artikel-Nr. 18, 01, 02, 07, 08, 30
	11	25019.9	2,80	500	Leiter 4,0 mm ²	für Presshülsen Artikel-Nr. 03, 04, 09
	13	25019.13	3,80	1000	rastbar für Leiter 2,5 mm ²	für Presshülsen Artikel-Nr. 18, 01, 02, 07, 08, 30
	14	25019.14	4,00	500	rastbar für Leiter 4,0 und 6,0 mm ²	für Presshülsen Artikel-Nr. 03, 04, 05, 06, 09